



ECO-SONIC® PANEL

SONIC ABSORBER PANELS core consists of a 6-7 lb. density rigid fiberglass board with no added formaldehyde. Resin hardened edges to reinforce panel perimeter against warping and damage. Your chosen finish selection is bonded directly to the panel face with all edges wrapped carefully and completely to the back of the panel to ensure a straight, flat, wrinkle-free surface with tailored corners.

A LARGE VARIETY OF STYLISH FINISHES including fabrics and vinyls are available. See the "Finishes" page on Lamvin.com for a direct link to our recommended suppliers' catalogs which include detailed images of an array of designs. Custom fabrics and printed fabrics are also options. All finishes shall be reviewed for panel stability.

APPLICATIONS:

- Schools
- Restaurants
- Any Place Where Urea-Formaldehyde Free Materials Are Required.

SPECIFICATIONS:

THICKNESS 1" | 2"

CUSTOM SHAPES MAX SIZE 4' × 10'

NRC 1" 1.09 | 2" 1.14

FIRE TEST ASTM E84-Class I/A

WALL MOUNTING OPTIONS



Z-Clip/Velcro



Z-Clip/Rail/ Velcro

CEILING MOUNTING OPTIONS







Impaling Clips w/ Adhesive



Rotofast™ Snap-On Anchor

EDGE OPTIONS



Mitered



Beveled



Radius



Pencil





Tegular Square













