



ACOUSTIC PANEL WITH LINEAR WOOD SLATS

Unite the highly effective acoustical performance of PET felt with the natural and attractive look of wood. Embrace continuity by creating a design that connects walls and ceilings. Installation is a breeze! Easily glue on or screw directly into any existing ceiling or wall. HUSHWOOD comes in four woodgrain options with a True Black PET backing.

LAMVIN

HUSHWOOD™

SPECIFICATIONS

Standard Panel Size: 24"x 96"

Thickness: 0.87"

Weight: 35 lbs/Panel

HARDWARE INCLUDED

HUSHWOOD comes ready to glue or screw to ceiling or wall

FIRE RATING

Class B per ASTM E-84

COMPOSITION

- 9mm 100% PET Felt
- MDF, Wood Veneer

ENVIRONMENTAL FACTORS

- 100% Recyclable
- 55% Post-Consumer Recycled
- Low VOC Emissions
- CARB-Approved TPC
- FSC Chain and Custody Certified



INSTALLATION OPTIONS

HUSHWOOD comes ready to glue or screw directly to any existing ceiling or wall. Screw directly on studs, and fit the screws between slats. Alternatively, HUSHWOOD can be cut to fit into a T-Grid similar to a typical dropped ceiling tile.

WALL INSTALLATION WITH FURRING STRIPS	WALL INSTALLATION WITH ADHESIVE	CEILING INSTALLATION WITH FURRING STRIPS	DROP CEILING INSTALLATION
--	--	---	--------------------------------------

WALL INSTALLATION WITH FURRING STRIPS VIDEO



ACOUSTICAL DATA

HUSHWOOD (22mm) no air gap: NRC = 0.55

HUSHWOOD (22mm) 1" air gap: NRC = 0.70

HUSHWOOD (22mm) 2" air gap: NRC = 0.80

Test reflects material ratings. Product testing according to standard mounting procedures coming soon. All NRC testing assumes one face/one object and does not account for the product thickness.

LAMVIN®

www.lamvin.com |     

 A CATALYST ACOUSTICS GROUP COMPANY