
HUSHWOOD™
A CATALYST ACOUSTICS GROUP BRAND
LAMVIN®



COMPOSITION:

- 9mm 100% PET Felt
- MDF, Wood Veneer

ENVIRONMENTAL FACTORS:

- 100% Recyclable
- 55% Post-Consumer Recycled
- Low VOC Emissions
- CARB-Approved TPC
- FSC Chain and Custody Certified

SPECIFICATIONS:

STANDARD PANEL SIZE 24”x 96”

THICKNESS 0.87”

WEIGHT 35 lbs/Panel

HARDWARE INCLUDED:

HUSHWOOD comes ready to glue or screw to ceiling or wall

FIRE RATING:

Class B per ASTM E-84

INSTALLATION OPTIONS:

- Wall Installation With Furring Strips
- Wall Installation With Adhesive
- Ceiling Installation With Furring Strips
- Drop Ceiling Installation

WALL INSTALLATION WITH FURRING STRIPS VIDEO

ACOUSTICAL DATA:

HUSHWOOD (22mm) no air gap: NRC = 0.55

HUSHWOOD (22mm) 1” air gap: NRC = 0.70

HUSHWOOD (22mm) 2” air gap: NRC = 0.80

Test reflects material ratings. Product testing according to standard mounting procedures coming soon. All NRC testing assumes one face/one object and does not account for the product thickness.